


# Serie Medium

## SR300 Nylon Cable Chain

### Inner height (D) 17 mm

Single link construction with anti-friction single-pin. Not openable. The chain is an extremely strong 18 mm chain, particularly suitable for high frequency/acceleration operations, like on laser cutting heads, in which the chain is highly stressed, due to high acceleration in all 3 directions.



### Pin

Part.no PG300

### Technical characteristics when self-supported


Speed	10 m/s
Acceleration	50 m/s <sup>2</sup>

For higher requirements please consult our technical dept.


A	B	C	D	R	Weight/m	Chain
mm	mm	mm	mm	mm	kg	Part Number
30	23	14	18	040-060-080-120	0,38	SR300015□□□*
41	23	25	18	040-060-080-120	0,43	SR300025□□□*
52	23	36	18	040-060-080-120	0,48	SR300035□□□*

\*Complete the code by inserting the value of the radius (R): Ex. SR300015 1 2 3

For sliding applications, technical data can slightly change according to frequency, added weight and environment.



R	H	N	M	N1	M1
mm	mm	mm	mm	mm	mm
40	103	85	185	185	385
60	143	105	248	410	865
80	183	125	315	545	1165
120	263	165	440	750	1640



Length of chain (L)



Half travel distance ( $\frac{LS}{2}$ )  
plus length of curve (M) or (M1)

$$L = \frac{LS}{2} + M \text{ or } M1$$



**Self-Supporting Capacity Diagram**

The maximum length of the self-supporting capacity ( $\frac{LS}{2}$ ) in relationship to the weight of the cables and hoses contained per linear metre.



The red marking in the diagram area considers the difference of weight between various widths of chain.

For applications with  $\frac{LS}{2}$  and weights not included in the area of the diagram showing self-supporting capacity, verify the possible use of support rollers (see page 30).

**Bright Zinc Plated Steel End Brackets\***

The end brackets set allows the two ends of the chain to be attached to the equipment.





Fig. A  
Chain fixed outside the radius. (Fig A)  
See end brackets mounting variations page 31.




**Bright Zinc Plated Steel Type Part Numbers**

Complete Set Assembled Chain	End Brackets Set
Type	Set
SR300015...	AP300KM <input type="checkbox"/> **
SR300025...	AG300KM <input type="checkbox"/> **
SR300035...	A300035KM <input type="checkbox"/> **

Complete Set Unassembled Chain	End Brackets Set
Type	Set
SR300015...	AP300K <input type="checkbox"/> **
SR300025...	AG300K <input type="checkbox"/> **
SR300035...	A300035K <input type="checkbox"/> **

\*Available on request in stainless steel  
\*\* 1=Pos.1; 2=Pos.2; 3=Pos.3  
See end brackets mounting variations page 31.



Suitable to long travel distance.  
To choose the guide channel see page 50

Special tool to remove the connecting pivots:  
Part Number PZ010.

For further information please consult Brevetti Stendalto's Technical Office